

03-13-00

A

03/09/00

Please type a plus sign (+) inside this box

PTO/SB/05 (4/98)
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.	003239.P059
First Inventor or Application Identifier	Mohammad R. Zonoun
Title	AUTOMATIC REMOTE COMMUNICATION USING NETWORK TELEPHONY
Express Mail Label No.	EL466333588US

APPLICATION ELEMENTS
See MPEP chapter 600 concerning utility patent application contents

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages 47]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 5]
4. Oath or Declaration [Total Pages]
 - a. ☐ Newly executed (original copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR §§ 1.63(d)(2) and 1.33(b).

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure Statement (IDS)/PTO - 1449 ☐ Copies of IDS Citations
11. ☐ Preliminary Amendment
12. ☐ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ *Small Entity Statement(s) ☐ Statement filed in prior application, Status still proper and desired
14. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
15. ☐ Other:

***NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).**

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____

Prior application Information: Examiner: _____ Group/Art Unit: _____

For **CONTINUATION** or **DIVISIONAL APPS** only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer Number of Bar Code Label (Insert Customer No. or Attach bar code label here) or ☒ Correspondence address below

Name	BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP				
Address	12400 Wilshire Boulevard, Seventh Floor				
City	Los Angeles	State	California	Zip Code	90025
Country	U.S.A.	Telephone	(714) 557-3800	Fax	(714) 557-3347

Name (Print/Type)	Thinh V. Nguyen, Reg. No. 42,034		
Signature		Date	03/09/00

Burden Hour Statement: This form is estimated to take 2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
1	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100

FOR

USING NETWORK TELEPHONY

Mohammad R. Zonoun

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP
12400 Wilshire Blvd., 7th Floor
Los Angeles, CA 90025-1026
(714) 557-3800

BACKGROUND

1. Field of the Invention

This invention relates to computer networks. In particular, the invention relates to network telephony.

5

2. Description of Related Art

Packet-based data networks are widely used to link various nodes, such as personal computers, servers, gateways, and so forth. Packet-based data networks include private networks, such as local area networks (LANs), Metropolitan Area Networks
10 (MANs), Wide Area Networks (WANs), and public networks, such as the Internet. The increased availability of such data networks has increased accessibility among nodes, whether the nodes are located in close proximity to each other (such as within an organization) or at far distances from each other. Popular forms of communications across such data networks include electronic mail, file transfer, web browsing, and other
15 exchanges of digital data>

With the increase capacity and reliability of data networks, voice communications over data networks, including private and public networks, have become possible. Voice communications over packet-based data networks are unlike voice communications in a conventional public switch telephone network (PSTN), which provides users with
20 dedicated end-to-end circuit connections for the duration of each call. Communications over data networks, such as IP (Internet Protocol) networks, are performed using packets that are sent in bursts from the source to one or more destination nodes. To enable voice communications between end points on a data network, a virtual circuit connection is established between the end points. Voice data sent over a data network has to share the

network bandwidth with conventional non-voice data (e.g., electronic mail, file transfer, web access, and other traffic). One standard that has been implemented for communications of voice as well as other data is the H.323 recommendation from the Telecommunications Sector of the International Telecommunication Union (ITU-T),
5 which describes terminals, equipment and services for multimedia communications over packet-based networks.

In an IP data network, each data packet is routed to a node having destination IP address contained within the header of each packet. Data packets may be routed over separate network paths before arriving at the final destination for reassembly.
10 Transmission speeds of the various packets may vary widely depending on the usage of data networks over which the data packets are transferred. During peak usage of data networks, delays added to the transfer of voice data packets may cause poor performance of voice communications.

Despite the increasing popularity of communicating over IP data networks,
15 several applications have presented difficulties to the integration of IP telephony in a traditional communication environment. One example is the Enhanced 911 (E911) emergency call. The E911 regulatory requirements require location information concerning where the 911 caller is located. With a switched network this problem was solved by the transmission of the caller's telephone number to a Public Safety Answering
20 Point (PSAP) where it was cross-referenced with an address database to determine the caller's location. That information was then displayed on a video monitor for the emergency dispatcher to direct public safety personnel responding to the emergency. This enabled emergency organizations to find callers who could not orally provide their precise location. Although this problem has been solved for conventional public
25 switched telephone systems such as in a public switched telephony network, the problem still exists for data networks, and in particular, location identification using IP telephony.

First, the IP telephones are not tied or physically connected to a geographical location and thus their locations may be dynamic. Second, the information retrieval is not scaleable because there are a large number of IP domains and service provider policies (e.g., telephone companies, cable companies, and cellular companies).

- 5 A further issue is that congestion on the data network may slow emergency communications traffic. Thus there is a need for prioritization of the emergency traffic to ensure a high degree of quality of service.

- 10 Since each IP address has no geographic association, there is no provision for locating a network resource such as a server, a router, a gateway, or an IP terminal. If a fault occurs in a network resource, there is no way of geographically locating that resource. Thus, it would be desirable to provide network resources with geographic information for the purpose of resource location. Furthermore, it would be desirable to locate the nearest network resource to a terminal in the event that the terminal cannot locate its geographic position.

- 15 In addition, IP telephony has been expensive to implement for applications involving the monitoring of environmental conditions, and remote meter reading, since each station required a dedicated connection to the IP network. Thus, there is a need for providing IP enabled applications with a communication means to communicate with a data network.

- 20 Therefore, there is a need in the art for an efficient and low-cost technique for automatic remote communication using telephony.

SUMMARY

The present invention is a method and apparatus to provide remote communication using network telephony. In a transmitter, an activation message is decoded to generate an activation command. The activation message is sent from an activator via a communication medium in response to a telephony call. An information message is transmitted, responsive to the activation command, to a receiver using a communication protocol. In a receiving unit, an activation message is decoded to generate an activation command. The activation message is sent in response to a telephony call. An information message is received, responsive to the activation command. The information message is sent from a transmitter according to a communication protocol via a communication medium.

According to one embodiment of the present invention, the information message includes a location identifier corresponding to location of the transmitter. The location identifier may be stored in advance or dynamically provided by GPS data. The communication protocol uses one of a multi-frequency tone, an ultra-red signal, a microwave signal, and an electromagnetic signal. The transmitter includes a modulator to modulate the information message according to a modulating scheme. The receiving unit includes a demodulator to demodulate the information message according to a demodulating scheme. The telephony call is made by a person located in proximity of the location of the transmitter. The telephony call may be one of an emergency call using an emergency call number, a transactional call for a commercial transaction, or an intrusive call.

The advantages of the invention include (1) provision of accurate, secure, and trusted location information, (2) compatibility with current telephony, computer devices,

BRIEF DESCRIPTION OF THE DRAWINGS

The features and advantages of the present invention will become apparent from the following detailed description of the present invention in which:

5 Figure 1 is a diagram illustrating a system according to one embodiment of the invention.

Figure 2 is a diagram illustrating a transmitter shown in Figure 1 according to one embodiment of the invention.

Figure 3 is a diagram illustrating a network component shown in Figure 1 according to one embodiment of the invention.

10 Figure 4 is a diagram illustrating a request subsystem shown in Figure 1 according to one embodiment of the invention.

Figure 5 is a flowchart illustrating a process for remote communication using network telephony according to one embodiment of the invention.

DESCRIPTION

The present invention is a method and apparatus to provide remote communication using network telephony. In a transmitter, an activation message is decoded to generate an activation command. The activation message is sent from an activator via a communication medium in response to a telephony call. An information message is transmitted, responsive to the activation command, to a receiver using a communication protocol. In a receiving unit, an activation message is decoded to generate an activation command. The activation message is sent in response to a telephony call. An information message is received, responsive to the activation command. The information message is sent from a transmitter according to a communication protocol via a communication medium.

According to one embodiment of the present invention, the information message includes a location identifier corresponding to location of the transmitter. The location identifier may be stored in advance or dynamically provided by GPS data. The communication protocol uses one of a multi-frequency tone, an ultra-red signal, a microwave signal, and an electromagnetic signal. The transmitter includes a modulator to modulate the information message according to a modulating scheme. The receiving unit includes a demodulator to demodulate the information message according to a demodulating scheme. The telephony call is made by a person located in proximity of the location of the transmitter. The telephony call may be one of an emergency call using an emergency call number, a transactional call for a commercial transaction, or an intrusive call. The emergency call number may be the "9-1-1" in the United States.

The advantages of the invention include (1) provision of accurate, secure, and trusted information, (2) compatibility with current telephony, computer devices, all

technologies, and regulatory requirements, (3) ease in integration and implementation, (4) low cost, and (5) readiness for industry acceptance and standardization.

In the following description, for purposes of explanation, numerous details are set forth in order to provide a thorough understanding of the present invention. However, it will be apparent to one skilled in the art that these specific details are not required in order to practice the present invention. In other instances, well-known electrical structures and circuits are shown in block diagram form in order not to obscure the present invention. For example, specific details are not provided as to whether the method is implemented in a station as a software routine, hardware circuit, firmware, or a combination thereof.

Embodiments of the invention may be represented as a software product stored on a machine-readable medium (also referred to as a computer-readable medium, a processor-readable medium, or a computer usable medium having a computer readable program code embodied therein). The machine-readable medium may be any type of magnetic, optical, or electrical storage medium including a diskette, compact disk read only memory (CD-ROM), memory device (volatile or non-volatile), or similar storage mechanism. The machine-readable medium may contain various sets of instructions, code sequences, configuration information, or other data. Those of ordinary skill in the art will appreciate that other instructions and operations necessary to implement the described invention may also be stored on the machine-readable medium. Software running from the machine readable medium may interface with circuitry to perform the described tasks.

Figure 1 is a diagram illustrating a system 100 according to one embodiment of the invention. The system 100 includes a satellite network 110, N transmitters 120₁ to

120_N, a communication medium 130, a network component 140, a network 150, a request subsystem 160, a transaction processor 170, and a network server 180.

The satellite network 110 includes a number of GPS satellites orbiting around the earth to provide GPS data 115 relating to positional information. The GPS data 115 is
5 received by the transmitters 120₁ to 120_N to determine the positional information.

The transmitters 120₁ to 120_N broadcast information to the network component 140 via the communication medium 130. The information from the transmitters 120₁ to 120_N are embedded in signals 125₁ to 125_N, respectively. The information may include location information, measurement information, or meter reading information. The
10 transmitters 120₁ to 120_N broadcast the information either at request upon receiving an activation request 135 from the request subsystem 160 or automatically, either on a substantially periodic basis or continuous basis. The communication medium 130 is any medium (e.g., air) that can carry the signals 125₁ to 125_N and the activation request 135. In one embodiment, the transmitters 120₁ to 120_N are geographically dispersed to form a
15 distributed location broadcast system. The location broadcast system is used in a number of applications that require the location information transmitted via IP telephony and/or computer network.

The network component 140 is a unit or subsystem that can be networked with other networkable components via the network 150. The network component 140
20 receives and processes the information transmitted or broadcast by at least one of the transmitters 120₁ to 120_N. The network 140 sends the processed information to other components connected to the network 150 such as the transaction processor 170 or the network server 180. The network component 140 is configured to be used in any applications that require receiving information (e.g., location information) from the
25 transmitters 120₁ to 120_N. These applications may include emergency call location

reporting (e.g., E911), commercial transactions (e.g., food delivery), intrusion detection (e.g., detecting location of an intrusive caller or harasser). The network component 140 may be an emergency server, or associated with a transactional entity 175 via the transaction processor 170.

- 5 The network 150 is any network that allows messages or data packets to be sent and received. The network 150 may be a data enabled PBX, a public switched telephone network (PSTN), a local area network (LAN), a wide area network (WAN), a metropolitan area network (MAN), an extranet, an intranet, or the Internet. The network 150 typically has some protocol or standard that allows voice and data to be transmitted
10 and received. In one embodiment, the network 150 is a data network having the voice over Internet Protocol (IP) capability. Protocols that govern the voice over IP may include the standards provided by the ITU such as the H.323 standard.

 The request subsystem 160 generates the activation request or message 135 to be sent to the transmitters to request for information in response to a telephony call 165.

- 15 The request subsystem 160 is connected to the network 150 to exchange network data with other network components. The telephony call 165 is a call that is processed by the IP telephony including voice calls and multimedia calls (e.g., teleconference call, audio and/or video call). The call is normally made by a person, or activated by a machine. The call may be made by a person who requests emergency assistance (e.g., E911), or a
20 person who requests a commercial transaction (e.g., food delivery), or an intruder who makes harassing calls to others.

- The transaction processor 170 performs transactional processing tasks in a transaction for a transactional entity 175. The transaction may be a commercial or a financial transaction. For example, the transaction entity 175 may be a food delivery
25 establishment who wishes to confirm or verify the location of the delivery destination.

The location information can be automatically sent from one of the transmitters 120₁ to 120_N to the transaction processor 170 via the network 150 when the person makes a telephony call 165. This automatic remote communication saves time and reduces error in getting the location information based on verbal communication. The transaction
5 processor 170 may have storage medium and display unit to automatically store and/or display the received information.

The network server 180 is a server that acts as a network gateway to provide interface to the network 150. The central authority 185 is an authority (e.g., local government, public utility) or station that receives the information sent by the
10 transmitters. For E911 applications, the central authority 190 is the Public Safety Answering Point (PSAP) and the information embedded in the signals includes the automatic number identification (ANI) and the automatic location identification (ALI). In environmental reporting applications, the central authority 185 may be an environmental data gathering agency that collects environmental data and distributes to news agencies or
15 other environmental agencies. In remote metering reading applications, the central authority 185 may be a public utility agency that collects the meter readings of utilities and records for load balancing, load monitoring, or billing purposes.

Figure 2 is a diagram illustrating one of the transmitters 120₁ to 120_N shown in Figure 1 according to one embodiment of the invention. The transmitter 120 includes a
20 reception unit 210, a transmission unit 220, a broadcast information 230, an information message 240, a location interface 255, a processor 280, and a memory 290.

The transmitter 120 is a device that transmits a signal 125 upon receiving the activation request 135 or continuously without request. In one embodiment of the invention, the transmitter 120 is a stand-alone device, in a wall or ceiling mountable case.
25 The transmitter 120 may alternatively be embedded in a building or any area where the

present invention might have application. In other embodiments of the invention, the transmitter 120 may be built into an always-on appliance such as a security system, a smoke detector, a server, a telephony apparatus, as an adjunct to an electrical or telecommunications socket or the like. For portable applications, such as when the

5 transmitter 120 is not fixed to a permanent location, the location interface 255 is a Global Positioning System (GPS) element for the provision of positional data. The location interface 255 processes received signals from orbiting satellites to derive positional information to an estimated mean accuracy of plus or minus 100 feet. Additionally, Differential GPS (DGPS) positioning techniques may be used, in which signals from a

10 local transmitter and orbiting satellites are processed to compute an extremely precise location, with a much smaller error than using conventional GPS techniques. Positional data may also be provided to the transmitter 120 from a device that calculates a position by processing signals from ground-based stations with fixed locations. Further, accurate altitude information may be calculated by a processor taking an input from a barometric

15 pressure sensor and a local barometric pressure setting. The local barometric pressure setting may be received automatically from a local weather reporting station, or over a network connection, for example, from a weather data provider. There are various techniques known in the art for deriving such positional information, and any one of these positioning devices may be coupled with transmitter 120.

20 Alternative to transmitting positional data, the transmitter 120 may transmit a predetermined code, wherein the code has an associated location that is registered with an address database. This code may be cross-referenced with the associated location.

In some embodiments, any of the above geographical locating methods and apparatus may be used in conjunction with the transmitter 120 when programming the

25 location information either into the device or when sending the location information to an

address database that stores geographical location information associated with a predetermined code.

In environmental reporting applications, the transmitter 120 is located near the environmental location. In remote meter reading applications, the transmitter 120 is
5 located near the meter. The signal 125 carries an information message to be sent over the network 150.

The reception unit 210 receives the activation request 135 sent from the request subsystem 160 (Figure 1). The reception unit 210 includes a transmitter decoder 212. The transmitter decoder 212 receives and decodes the activation request/ message 135. In
10 most cases, the transmitter decoder 212 is a signal detector that detects the signal carrying the activation request 135. The signal carrying the activation request 135 may be a signal having a predefined frequency, code, or bit pattern and the signal detector is designed to detect any signal with that predefined frequency, code, or bit pattern. The reception unit 210 generates an activation command 215 to the transmission unit 220. The transmission
15 unit 220 receives the activation command 215 and retrieves the broadcast information 230. The transmission unit 220 includes a modulator 222 which modulates the broadcast information 230 according to a pre-defined communication protocol that is designed to be compatible with the network component 140. The modulated information message 230 becomes one of the signals 125_1 to 125_N to be transmitted over the communication
20 medium 130. The signal 125 may be any one of a multi-frequency (MF) signal, an ultra-red signal, an infra-red signal, a microwave signal, a RF signal, or any other electromagnetic or optical signal.

In one embodiment, the signal modulation uses a pseudo random binary sound (PRBS) technique. The PRBS codes can generate many different code sequences and
25 therefore can help differentiate many different locations. In other words, several

transmitters can be installed in close proximity without having too much interference.

The PRBS signal behaves like white noise and is therefore less intrusive and would not

cause interference to other signal transmissions. Lastly, the PRBS signal level can be

very low, resulting in low power consumption, such that the transmitter can be turned on

5 all the time. In this case, it is possible that there is no need to have a transmitter activator.

When the telephony number is detected, it is only necessary to activate the receiver to

receive the PRBS signal.

The broadcast information 230 is the information to be transmitted by the

transmission unit 220. The broadcast information 230 incorporates the contents of the

10 information message with other information and includes any one of an identification tag

232, an absolute location 234, a relative location 236, and other information 238. The

broadcast information 230 is arranged according to a predefined format that can be

identified and decoded by the network component 140. The absolute and relative

locations 234 and 236 are used in applications requiring location information such as the

15 GPS data. The absolute location corresponds to an absolute reference to a location. The

absolute reference includes geographical coordinates such as longitudinal and latitudinal

data.

The information message 240 is any message that is to be sent to network 175

according to the application in which this invention is practiced. There are numerous

20 applications that the remote communication technique in this invention can be used.

Some examples of these applications include emergency reporting (e.g., E911),

geographical location reporting, geographical location verification, information gathering,

environmental conditions reporting, remote meter reading, electronic commerce,

commercial transactions, and intrusion detection.

such as electricity, water, or gas consumption at the facility that the transmitter 120 is installed. The information message 240 may be constantly updated or updated only at the time of activation to reflect the current reading of the meter.

The processor 280 is typically an embedded micro-controller that can execute
5 code to control the operation of the transmitter 120. In some applications, the processor 280 may be optional. The processor 280 is interfaced to the memory 290. The memory 290 may include a random access memory (RAM) and/or read only memory (ROM) to store program code or data. The processor 280 executes computer readable program code for decoding the activation message 135, modulating the broadcast information 230, and
10 transmitting the signal 125 to the communication medium 130.

Figure 3 is a diagram illustrating the network component 140 shown in Figure 1 according to one embodiment of the invention. The network component 140 includes a receiving unit 310, a location determination unit 320, a network interface 330, a receiver decoder 340, a receiver activator 350, a processor 360, and a memory 370.

15 The receiving unit 310 receives the signal 125 sent from the transmitters 120. The receiving unit 310 is activated by an activation command 315 from the receiver decoder 340 and is enabled to receive the signal 125 carrying the broadcast information 230 (Figure 2). The receiving unit 310 includes a demodulator 312 to demodulate the received signal 125 and provides the extracted information message 315. The extracted
20 information message 315 is essentially the same as the information message 240 (Figure 2). The receiving unit 310 then sends the extracted information message 315 to the location determination unit 320. The location determination unit 320 is used in applications that require the location information. The location determination unit 320 determines the location embedded in the extracted information message 315. This may

include calculations of x, y, z coordinates based on the GPS data, distance estimates, or any other necessary calculations.

The network interface 330 allows the network component 140 to interface to the network 150. The network interface 330 includes a data packet 335 to be sent to other
5 networked components. The data packet 335 includes the extracted information message 315.

The processor 360 is typically an embedded micro-controller that can execute code to control the operation of the network component 140. The processor 360 may be a media processor with telephony capabilities or a digital signal processor (DSP) to
10 perform other signal processing tasks. In some applications, the processor 360 may be optional. Processor 360 may also be implemented by other control means such as a dedicated logic circuitry, programmable gate array (PGA), a microcontroller, a microprocessor, a an application specific integrated circuit (ASIC), or hybrids of these. The processor 360 is interfaced to the memory 370. The memory 370 may include a mass
15 storage device (e.g., CD ROM, floppy drive, hard disk drive), random access memory (RAM) and/or read only memory (ROM) to store program code or data. The processor 360 executes computer readable program code for decoding the activation message 345, demodulating the signal 125, and generating the extracted information message 315.

The receiver decoder 340 decodes an activation command 315 sent from the
20 receiver activator 350 when the signal 125 is to be received. The receiver activator 350 may be connected to the receiver decoder 340 via an electronic interface such as a parallel data interface or a serial data interface over a serial data bus, or an electromechanical switching mechanism such as a relay. The receiver activator 350 may be a software program code executed by the processor 360, or a hardware mechanism controlled by the

processor 360. The receiver activator 350 sends an activation message 345 to the receiver decoder 340 in response to the telephony call 165.

Figure 4 is a diagram illustrating the request subsystem 160 shown in Figure 1 according to one embodiment of the invention. The request subsystem 160 includes a telephony call device 410, a telephony interface 420, a telephony server 430, a telephony connection path 440, and a transmitter activator 450. In some applications, not all of the elements in the request subsystem 160 are necessary.

The call device 410 is a device that provides telephony service and transmits the telephony call 165. The call device 410 may be a telephone unit 412, a computer 414 (e.g., a notebook, a personal digital assistant, a laptop, and a desktop computer) with telephony capabilities, and a cellular telephony device 416. A person can use the call device 410 in any place or location. For example, a person can use the call device 410 at home, in a hotel room, or in a public telephony booth.

The telephony interface 420 provides telephony services to the call device 410. The telephony interface 420 is optional in some instances. The telephony services include multimedia interface for voice over Internet Protocol (IP) or any other protocols. The telephony interface 420 may include a router, a gateway, or a private branch exchange (PBX) with IP telephony capabilities. The PBX routes the call made by the call device 410 through the server 430 via some programmed trunk interface. In another embodiment, the telephony interface 420 may be a device to listen to the dialed tone, or call setup signaling and detect if a certain number (e.g., 911) has been called.

The server 430 is typically installed near or at the location of the call device 410. The server 430 is connected to the network 150 and/or directly to the transmitter activator 450 to exchange network data/messages. The server 430 may be an IP gateway that allows the call to be embedded in a network data to be sent over the network 150. The

server 430 may be a centralized computer system that has a database 432 for telephony services. The database 432 may include a directory of telephony numbers or people. The telephony numbers are those that need to be detected when a telephony call is made via the telephony device 410. For example, the database 432 may include the 911 number for E911 service, a phone number of a utility agency to report meter readings (e.g., for gas, water, electricity usage), a phone number of an environmental bureau to report environmental conditions (e.g., temperature, humidity). In other applications, the database 432 may include any telephony numbers that may utilize the remote communication technique in this invention. For example, businesses may find it desirable to automatically locate the calling party or to verify the location of the calling party before placing an order for a product or service. Such a need arises, for example, with food delivery companies, when receiving orders from customers via a telephony device. Thus, these business may subscribe to having their number included in database 432, such that the connection to that number causes the transmitter 120 to activate, as further described below.

The telephony connection path 440 is the telephony link that links the IP telephony interface 420 and/or the call device 410. The telephony connection path 440 may be a traditional telephony line in a home or in a business environment, a connection to a data network such as a LAN, a WAN, or a MAN, or a wireless interface to the cellular telephony 416.

The transmitter activator 450 is connected to the telephony connection path 440 and/or the server 430. The transmitter activator 450 may be integral to the server 430 or the telephony interface 420. The transmitter activator 450 sends an activation request or message 135 to the transmitter 120 via the communication medium 130 in response to a telephony call 165 made by the call device 410. In one embodiment, the communication medium 130 is air and the activation request or message 135 is modulated into any one of

a multi-frequency (MF) signal, an ultra-red signal, an infra-red signal, a microwave signal, an RF signal, or any other electromagnetic or optical signal. In one embodiment, the transmitter activator 450 is interfaced to the server 430 and receives a command from the server 430 when a specified telephony number (e.g., 911) is detected. In another
5 embodiment, the transmitter activator 450 is interfaced to the telephony connection path 440 to detect if a specified number is being dialed. For example, in a home environment, the transmitter activator 450 is a device installed at the telephone box to listen to the telephone tone being dialed. When the specified telephony number (e.g., 911) is detected, the transmitter activator 450 sends the activation request or message 135 to the
10 transmitter 120.

Figure 5 is a flowchart illustrating a process 500 for remote communication using network telephony according to one embodiment of the invention.

Upon START, a telephony call is placed via a call device (Block 510). The call device may be a regular telephony handset, a cellular phone, or a notebook computer with
15 audio interface capabilities. Then, the process 500 determines if the number dialed is the specified number (e.g., 911) (Block 515). If not, the process 500 proceeds to process the call as normal (Block 520) and is then terminated. Otherwise, the process 500 activates the transmitter by sending an activation request or message (Block 525).

Then, the process 500 decodes the activation message at the transmitter (Block
20 530). The decoding may simply involve detecting a signal with a specified characteristic (e.g., specified frequency, code). Next, the process 500 retrieves and sends the information message (e.g., location identifier) to a receiver via a communication medium (Block 535). The sending of the information message may involve modulating the information message according to a communication protocol.

Then, the process 500 determines if the information has been reliably received (Block 540). If not, the process 500 generates an error condition (Block 545) and is then terminated. Otherwise, the process 500 de-activates the transmitter (Block 550). Next, the process 500 receives the signal sent over the communication medium (Block 555).

- 5 Then, the process 500 demodulates the received signal to extract the information message (Block 560). Next, the process 500 embeds the extracted information message in network data in a data packet (Block 565). Then, the process 500 sends the network data in the data packet via the network (Block 560). Next, the process 500 receives the data packet with the information message (Block 565). The process 500 is then terminated.

- 10 While this invention has been described with reference to illustrative embodiments, this description is not intended to be construed in a limiting sense. Various modifications of the illustrative embodiments, as well as other embodiments of the invention, which are apparent to persons skilled in the art to which the invention pertains are deemed to lie within the spirit and scope of the invention.

15

What is claimed is:

- 1 1. An apparatus comprising:

2 a decoder to decode an activation message, the activation message being sent from
3 an activator via a communication medium in response to a telephony call, the decoder
4 generating an activation command; and

5 a transmitter coupled to the decoder to transmit an information message, to a
6 receiver using a communication protocol, the transmitter being responsive to the
7 activation command.
- 1 2. The apparatus of claim 1 wherein the receiver is coupled to a server, the
2 server embedding the information message in network data to be sent over a network.
- 1 3. The apparatus of claim 1 wherein the communication protocol uses one of
2 a multi-frequency tone, an ultra-red signal, a microwave signal, and an electromagnetic
3 signal.
- 1 4. The apparatus of claim 1 wherein the transmitting unit comprises a
2 modulator to modulate the information message according to a modulating scheme.

1 5. The apparatus of claim 4 wherein the modulating scheme is compatible
2 with a sound signal.

1 6. The apparatus of claim 5 wherein the modulating scheme uses a pseudo
2 random binary sound (PRBS).

1 7. The apparatus of claim 1 wherein the information message includes a
2 location identifier corresponding to location of the transmitter.

1 8. The apparatus of claim 7 wherein the location identifier includes global
2 positioning system (GPS) information.

1 9. The apparatus of claim 7 wherein the telephony call is made by a person
2 located in proximity of the location of the transmitter.

1 10. The apparatus of claim 7 wherein the telephony call is an emergency call
2 using an emergency call number.

1 11. An apparatus comprising:
2 a decoder to decode an activation message, the activation message being sent from
3 an activator in response to a telephony call, the decoder generating an activation
4 command; and

5 a receiving unit coupled to the decoder to receive an information message
6 responsive to the activation command, the information message being sent from a
7 transmitter according to a communication protocol via a communication medium.

1 12. The apparatus of claim 11 wherein the receiving unit is coupled to a
2 server, the server embedding the information message in network data to be sent over a
3 network.

1 13. The apparatus of claim 12 wherein the communication protocol uses one
2 of a multi-frequency tone, an ultra-red signal, a microwave signal, and an electromagnetic
3 signal.

1 14. The apparatus of claim 13 wherein the receiving unit comprises a
2 demodulator to demodulate the information message according to a demodulating
3 scheme.

1 15. The apparatus of claim 14 wherein the demodulating scheme is compatible
2 with a sound signal.

1 16. The apparatus of claim 15 wherein the demodulating scheme uses a
2 pseudo random binary sound (PRBS).

1 17. The apparatus of claim 11 wherein the information message includes a
2 location identifier corresponding to location of the transmitting unit.

1 18. The apparatus of claim 17 wherein the location identifier includes global
2 positioning system (GPS) information.

1 19. The apparatus of claim 18 wherein the telephony call is made by a person
2 located in proximity of the transmitter.

1 20. The apparatus of claim 19 wherein the telephony call is an emergency call
2 using an emergency call number.

1 21. A network comprising a plurality of commonly coupled location
2 transmitters, each transmitter comprising a transmission unit to broadcast respective
3 location information.

1 22. The network of Claim 21, wherein the transmission unit of a transmitter
2 broadcasts the respective location information on a substantially periodic basis.

1 23. The network of Claim 21, wherein the transmission unit of a transmitter
2 broadcasts the respective location information on a substantially continuous basis.

1 24. The network of Claim 21, wherein the transmission unit of a transmitter
2 broadcasts the respective location information responsive to an activation request.

1 25. The network of Claim 24, wherein at least one of the plurality of
2 transmitters comprises
3 a reception unit coupled to the transmission unit of the at least one of the plurality
4 of transmitters, the reception unit to receive the activation request and to notify the
5 transmission unit of such receipt.

1 26. The network of Claim 21, wherein each transmitter further comprises a
2 reception unit coupled to the transmission unit to receive an activation request and to

3 notify the transmission unit of such receipt; and wherein the reception units of a set of the
4 transmitters to receive the activation request at substantially the same time.

1 27. The network of Claim 26, wherein the set of the transmitters comprises all
2 of the plurality of transmitters in the network.

1 28. The network of Claim 26, wherein the set of the transmitters comprises
2 less than all of the plurality of transmitters in the network.

1 29. The network of Claim 21, wherein the transmitters are geographically
2 dispersed to form a distributed location broadcast system.

1 30. The network of Claim 21, wherein the transmission unit of a transmitter
2 broadcasts respective broadcast information in a format consistent with at least one of an
3 identification tag, an absolute location, and a relative location.

1 31. The network of Claim 21, further comprising:

2 a network component capable of coupling to a first transmitter of the plurality of
3 transmitters to receive and process the respective location information broadcast by the
4 first transmitter.

1 32. The network of Claim 24, further comprising:
2 a server coupled to the plurality of transmitters to selectively issue the activation
3 request to the plurality of transmitters.

1 33. The network of Claim 24, further comprising:
2 a network component capable of sensing at least one of the plurality of
3 transmitters, the network component comprising:
4 a sensor capable of at least intermittent coupling to a first transmitter of
5 the plurality of transmitters to receive the respective location broadcast by the first
6 transmitter, a location determination unit coupled to the sensor to process the
7 received respective location information, and a network interface to externally
8 issue the respective location information in accordance with a packet data format.

1 34. The network of Claim 33, further comprising:
2 a server coupled to the plurality of transmitters to selectively issue the activation
3 request to the plurality of transmitters responsive to a location event; and
4 a packet network interposing the network interface of the network component and
5 the server, the packet network to bear the packetized, respective location information to
6 said server.

1 35. The network of Claim 34, wherein the location event is generated by the
2 network component.

1 36. The network of Claim 35, wherein the location event comprises an
2 emergency call.

1 37. The network of Claim 34, further comprising an e-commerce transaction
2 processor coupled to the packet network, wherein the location event is generated by the e-
3 commerce transaction processor.

1 38. A method of locating a networkable component, comprising:
2 receiving a location information request, the location information request
3 requiring a location information;
4 generating at least one data packet comprising the location information; and
5 transmitting the at least one data packet in response to the location information
6 request.

1 39. The method of claim 38, wherein the data packet complies with Internet
2 Protocol.

1 40. The method of claim 38, wherein the receiving of the location information
2 is performed by a receiver.

1 41. The method of claim 38, further comprising:
2 storing the location information in a store for storing location information.

1 42. The method of claim 38, further comprising:
2 receiving the location information from a location information receiving device.

1 43. The method of claim 42, wherein the location information receiving
2 device is a Global Positioning System receiver.

1 44. The method of claim 38, wherein the location information is an absolute
2 reference to a location.

1 45. The method of claim 44, wherein the absolute reference comprises
2 geographic coordinates.

1 46. The method of claim 44, wherein the absolute reference contains a
2 location address.

1 47. The method of claim 44, wherein the absolute reference comprises Global
2 Positioning System data.

1 48. The method of claim 38, wherein the location information comprises a
2 relative reference to a location.

1 49. The method of claim 38, wherein the location information comprises a
2 predetermined code associated with a location.

1 50. The method of claim 38, wherein the location information request is
2 generated in response to an emergency telephony call.

1 51. The method of claim 38, wherein the location information request
2 originates from a networkable component.

1 52. The method of claim 51, wherein the networkable component is an
2 emergency server.

1 53. The method of claim 51, wherein the networkable component comprises
2 an association with a commercial transaction.

1 54. A networkable component comprising:
2 a receiver for receiving location information in response to a telephony call;
3 a processor for processing location information; and
4 a network interface for transmitting the location information over a network.

1 55. The networkable component of claim 54 wherein the location information
2 is one of a pre-determined location information and a global positioning system (GPS)
3 information.

1 56. The networkable component of claim 55 wherein the telephony call is one
2 of an emergency call, a commercial transaction call, and an intrusive call.

1 57. A networkable component comprising:
2 means for receiving location information in response to a telephony call;
3 means for processing location information; and
4 interface means for transmitting the location information

1 58. The networkable component of claim 57 wherein the location information
2 is one of a pre-determined location information and a global positioning system (GPS)
3 information.

1 59. The networkable component of claim 58 wherein the telephony call is one
2 of an emergency call, a commercial transaction call, and an intrusive call.

1 60. A networkable component comprising:
2 a location sensor to provide location information;
3 a determination unit coupled to the sensor, the determination unit to determine the
4 location information; and
5 a network interface coupled to the determination unit to selectively transmit the
6 location information over a network.

1 61. A method comprising:
2 decoding an activation message to generate an activation command, the activation
3 message being sent from an activator via a communication medium in response to a
4 telephony call; and
5 transmitting an information message responsive to the activation command, by a
6 transmitting unit, to a receiver using a communication protocol.

1 62. The method of claim 61 further comprising embedding the information
2 message in network data to be sent over a network.

1 63. The method of claim 61 wherein the communication protocol uses one of
2 a multi-frequency tone, an ultra-red signal, a microwave signal, and an electromagnetic
3 signal.

1 64. The method of claim 61 wherein transmitting comprises modulating the
2 information message according to a modulating scheme.

1 65. The method of claim 64 wherein the modulating scheme is compatible
2 with a sound signal.

1 66. The method of claim 64 wherein the modulating scheme uses a pseudo
2 random binary sound (PRBS).

1 67. The method of claim 61 wherein the information message includes a
2 location identifier corresponding to location of the transmitting unit.

1 68. The method of claim 67 wherein the location identifier includes global
2 positioning system (GPS) information.

1 69. The method of claim 61 wherein the telephony call is made by a person
2 located in proximity of the location of the transmitter.

1 70. The method of claim 69 wherein the telephony call is an emergency call
2 using an emergency call number.

1 71. A method comprising:
2 decoding an activation message to generate an activation command, the activation
3 message being sent from an activator in response to a telephone call; and

4 receiving an information message responsive to the activation command, the
5 information message being sent from a transmitter according to a communication
6 protocol.

1 72. The method of claim 71 further comprises embedding the information
2 message in network data to be sent over a network.

1 73. The method of claim 72 wherein the communication protocol uses one of
2 a multi-frequency tone, an ultra-red signal, a microwave signal, and an electromagnetic
3 signal.

1 74. The method of claim 73 wherein receiving comprises demodulating the
2 information message according to a demodulating scheme.

1 75. The method of claim 74 wherein the demodulating scheme is compatible
2 with a sound signal.

1 76. The method of claim 75 wherein the demodulating scheme uses a pseudo
2 random binary sound (PRBS).

1 77. The method of claim 71 wherein the information message includes a
2 location identifier corresponding to location of the transmitter.

1 78. The method of claim 77 wherein the location identifier includes global
2 positioning system (GPS) information.

1 79. The method of claim 78 wherein the telephony call is made by a person
2 located in proximity of the transmitter.

1 80. The method of claim 76 wherein the telephony call is an emergency call
2 using an emergency call number.

1 81. A computer program product comprising:
2 a machine useable medium having computer program code embedded therein, the
3 computer program product having:
4 computer readable program code for decoding an activation message to generate
5 an activation command, the activation message being sent from an activator via a
6 communication medium in response to a telephony call; and

7 computer readable program code for transmitting an information message,
8 responsive to the activation command by a transmitting unit, to a receiver using a
9 communication protocol.

1 82. The computer program product of claim 81 further comprises computer
2 readable program code for embedding the information message in network data to be sent
3 over a network.

1 83. The computer program product of claim 82 wherein the communication
2 protocol uses one of a multi-frequency tone, an ultra-red signal, a microwave signal, and
3 an electromagnetic signal.

1 84. The computer program product of claim 83 wherein the computer readable
2 program code for transmitting comprises computer readable program code for modulating
3 the information message according to a modulating scheme.

1 85. The computer program product of claim 84 wherein the modulating
2 scheme is compatible with a sound signal.

1 86. The computer program product of claim 85 wherein the modulating
2 scheme uses a pseudo random binary sound (PRBS).

1 87. The computer program product of claim 81 wherein the information
2 message includes a location identifier corresponding to location of the transmitting unit.

1 88. The computer program product of claim 82 wherein the location identifier
2 includes global positioning system (GPS) information.

1 89. The computer program product of claim 88 wherein the telephony call is
2 made by a person located in proximity of the location of one of the decoder and the
3 transmitter.

1 90. The computer program product of claim 89 wherein the telephony call is
2 an emergency call using an emergency call number.

1 91. A computer program product comprising:

2 a machine useable medium having computer program code embedded therein, the
3 computer program product having:

4 computer readable program code for decoding an activation message to generate
5 an activation command, the activation message being sent from an activator in response
6 to a telephony call; and

7 computer readable program code for receiving an information message,
8 responsive to the activation command, the information message being sent from a
9 transmitter according to a communication protocol.

1 92. The computer program product of claim 91 further comprises computer
2 readable program code for embedding the information message in network data to be sent
3 over a network.

1 93. The computer program product of claim 92 wherein the communication
2 protocol uses one of a multi-frequency tone, an ultra-red signal, a microwave signal, and
3 an electromagnetic signal.

1 94. The computer program product of claim 93 wherein the computer readable
2 program code for receiving comprises demodulating the information message according
3 to a demodulating scheme.

1 95. The computer program product of claim 94 wherein the receiver is a tone
2 receiver compatible with the demodulating scheme.

1 96. The computer program product of claim 95 wherein the demodulating
2 scheme uses a pseudo random binary sound (PRBS).

1 97. The computer program product of claim 91 wherein the information
2 message includes a location identifier corresponding to location of the transmitter.

1 98. The computer program product of claim 97 wherein the location identifier
2 includes global positioning system (GPS) information.

1 99. The computer program product of claim 98 wherein the telephony call is
2 made by a person located in proximity of the location of the transmitting unit.

1 100. The computer program product of claim 99 wherein the telephony call is
2 an emergency call using an emergency call number.

1 101. A system comprising:
2 an activator to transmit an activation message in response to a telephony call; and
3 a transmitter to communicate with the activator via a communication medium, the
4 transmitter comprising:
5 a decoder to decode the activation message, the decoder generating an
6 activation command, and

7 a transmitting unit coupled to the decoder to transmit an information
8 message, responsive to the activation command, to a receiver using a
9 communication protocol.

1 102. The system of claim 101 wherein the receiver is coupled to a server, the
2 server embedding the information message in network data to be sent over a network.

1 103. The system of claim 102 wherein the communication protocol uses one of
2 a multi-frequency tone, an ultra-red signal, a microwave signal, and an electromagnetic
3 signal.

1 104. The system of claim 103 wherein the transmitting unit comprises a
2 modulator to modulate the information message according to a modulating scheme.

1 105. The system of claim 104 wherein the modulating scheme is compatible
2 with a sound signal.

1 106. The system of claim 105 wherein the modulating scheme uses a pseudo
2 random binary sound (PRBS).

1 107. The system of claim 101 wherein the information message includes a
2 location identifier corresponding to location of the transmitter.

1 108. The system of claim 107 wherein the location identifier includes global
2 positioning system (GPS) information.

1 109. The system of claim 108 wherein the telephony call is made by a person
2 located in proximity of the location of one of the decoder and the transmitter.

1 110. The system of claim 109 wherein the telephony call is an emergency call
2 using an emergency call number.

1 111. A system comprising:
2 an activator to transmit an activation message in response to a telephony call; and
3 a receiver coupled to the server, the receiver comprising:
4 a decoder to decode the activation message, the decoder generating an
5 activation command, and

6 a receiving unit coupled to the decoder to receive an information message
7 responsive to the activation command, the information message being sent from a
8 transmitter according to a communication protocol via a communication medium.

1 112. The system of claim 111 further comprises a server coupled to the receiver
2 to embed the information message in network data to be sent over a network.

1 113. The system of claim 112 wherein the communication protocol uses one of
2 a multi-frequency tone, an ultra-red signal, a microwave signal, and an electromagnetic
3 signal.

1 114. The system of claim 113 wherein the receiver comprises a demodulator to
2 demodulate the information message according to a demodulating scheme.

1 115. The system of claim 114 wherein the demodulating scheme is compatible
2 with a sound signal.

1 116. The system of claim 115 wherein the demodulating scheme uses a pseudo
2 random binary sound (PRBS).

1 117. The system of claim 111 wherein the information message includes a
2 location identifier corresponding to location of the transmitter.

1 118. The system of claim 117 wherein the location identifier includes global
2 positioning system (GPS) information.

1 119. The system of claim 118 wherein the telephony call is made by a person
2 located in proximity of the location of the transmitter.

1 120. The system of claim 119 wherein the telephony call is an emergency call
2 using an emergency call number.

ABSTRACT OF THE DISCLOSURE

The present invention is a method and apparatus to provide remote communication using network telephony. In a transmitter, an activation message is decoded to generate an activation command. The activation message is sent from an activator via a communication medium in response to a telephony call. An information message is transmitted, responsive to the activation command, to a receiver using a communication protocol. In a receiver, an activation message is decoded to generate an activation command. The activation message is sent in response to a telephone call. An information message is received, responsive to the activation command. The information message is sent from a transmitter according to a communication protocol via a communication medium.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209

000000 222250

100




FIG. 1

120
↓




FIG. 2




FIG. 5

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below, next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or any original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

AUTOMATIC REMOTE COMMUNICATION USING NETWORK TELEPHONY

the specification of which ☒ is attached hereto.
☐ was filed on _____ as
United States Application Number _____
or PCT International Application Number _____
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment referred to above. I do not know and do not believe that the claimed invention was ever known or used in the United States of America before my invention thereof, or patented or described in any printed publication in any country before my invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, and that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months (for a utility patent application) or six months (for a design patent application) prior to this application.

I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d), of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s):

APPLICATION NUMBER	COUNTRY (OR INDICATE IF PCT)	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 37 USC 119
			<input type="checkbox"/> No <input type="checkbox"/> Yes
			<input type="checkbox"/> No <input type="checkbox"/> Yes
			<input type="checkbox"/> No <input type="checkbox"/> Yes

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below:

APPLICATION NUMBER	FILING DATE

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

APPLICATION NUMBER	FILING DATE	STATUS (ISSUED, PENDING, ABANDONED)

I hereby appoint the persons listed on Appendix A hereto (which is incorporated by reference and a part of this document) as my respective patent attorneys and patent agents, with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith.

Send correspondence to:

Thinh V. Nguyen, Reg. No. 42,034, BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN, LLP
(Name of Attorney or Agent)
12400 Wilshire Boulevard, 7th Floor, Los Angeles, California 90025 and direct telephone calls to:
Thinh V. Nguyen, (714) 557-3800.
(Name of Attorney or Agent)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole/First Inventor (given name, family name) Mohammad R. Zonoun

Inventor's Signature _____ Date _____

Residence Sunnyvale, California USA Citizenship Iran/USA
(City, State) (Country)

P. O. Address 772 Dartshire Way
Sunnyvale, California 94087 USA

Full Name of Second/Joint Inventor (given name, family name) _____

Inventor's Signature _____ Date _____

Residence _____ Citizenship _____
(City, State) (Country)

P. O. Address _____

Appendix A

I hereby appoint BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP, a firm including: William E. Alford, Reg. No. 37,764; Farzad E. Amini, Reg. No. 42,261; Amy M. Armstrong, Reg. No. 42,265; Aloysius T. C. AuYeung, Reg. No. 35,432; William Thomas Babbitt, Reg. No. 39,591; Carol F. Barry, Reg. No. 41,600; Jordan Michael Becker, Reg. No. 39,602; Bradley J. Berezna, Reg. No. 33,474; Michael A. Bernadieu, Reg. No. 35,934; Roger W. Blakely, Jr., Reg. No. 25,831; Gregory D. Caldwell, Reg. No. 39,926; Ronald C. Card, Reg. No. 44,587; Thomas M. Coester, Reg. No. 39,637; Michael Anthony DeSanctis, Reg. No. 39,957; Daniel M. De Vos, Reg. No. 37,813; Robert Andrew Diehl, Reg. No. 40,992; Matthew C. Fagan, Reg. No. 37,542; Tarek N. Fahmi, Reg. No. 41,402; James Y. Go, Reg. No. 40,621; James A. Henry, Reg. No. 41,064; Willmore F. Holbrow III, Reg. No. 41,845; Sheryl Sue Holloway, Reg. No. 37,850; George W. Hoover II, Reg. No. 32,992; Eric S. Hyman, Reg. No. 30,139; Dag H. Johansen, Reg. No. 36,172; William W. Kidd, Reg. No. 31,772; Eric T. King, Reg. No. 44,188; Erica W. Kuo, Reg. No. 42,775; Michael J. Mallie, Reg. No. 36,591; Paul A. Mendonsa, Reg. No. 42,879; Darren J. Milliken, Reg. No. 42,004; Chun M. Ng, Reg. No. 36,878; Thien T. Nguyen, Reg. No. 43,835; Thinh V. Nguyen, Reg. No. 42,034; Dennis A. Nicholls, Reg. No. 42,036; Lisa A. Norris, Reg. No. 44,976; Daniel E. Ovanezian, Reg. No. 41,236; Babak Redjaian, Reg. No. 42,096; William F. Ryann, Reg. No. 44,313; James H. Salter, Reg. No. 35,668; William W. Schaal, Reg. No. 39,018; James C. Scheller, Reg. No. 31,195; Jeffrey S. Smith, Reg. No. 39,377; Maria McCormack Sobrino, Reg. No. 31,639; Stanley W. Sokoloff, Reg. No. 25,128; Judith A. Szepesi, Reg. No. 39,393; Vincent P. Tassinari, Reg. No. 42,179; Edwin H. Taylor, Reg. No. 25,129; George G. C. Tseng, Reg. No. 41,355; Joseph A. Twarowski, Reg. No. 42,191; Lester J. Vincent, Reg. No. 31,460; Glenn E. Von Tersch, Reg. No. 41,364; John Patrick Ward, Reg. No. 40,216; Charles T. J. Weigell, Reg. No. 43,398; Kirk D. Williams, Reg. No. 42,229; James M. Wu, Reg. No. P45,241; Steven D. Yates, Reg. No. 42,242; and Norman Zafman, Reg. No. 26,250; my attorneys; and Andrew C. Chen, Reg. No. 43,544; Justin M. Dillon, Reg. No. 42,486; Paramita Ghosh, Reg. No. 42,806; Sang Hui Kim, Reg. No. 40,450; and John F. Travis, Reg. No. 43,203; my patent agents, with offices located at 12400 Wilshire Boulevard, 7th Floor, Los Angeles, California 90025, telephone (714) 557-3800, with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith.